

Technical data sheet Optical data transmission

Part no.: 50039940

DDLS 200/200.2-50

Contents

- Technical data
- Electrical connection
- Operation and display
- Suitable transmitters



For illustration purposes only



CANopen

DeviceNet

Technical data

Basic data

| | |
|--------|----------|
| Series | DDLS 200 |
|--------|----------|

Special version

| | |
|-----------------|---|
| Special version | Not influenced by reflective surfaces Operation of parallel light axes |
|-----------------|---|

Optical data

| | |
|------------------------|--------------------|
| Working range | 200 ... 200,000 mm |
| Light source | LED |
| Transmission frequency | F2 |
| Opening angle | 1 ° |

Electrical data

Performance data

| | |
|----------------------|-----------------|
| Supply voltage U_B | 18 ... 30 V, DC |
|----------------------|-----------------|

Inputs

| | |
|------------------------------------|------------|
| Number of digital switching inputs | 1 Piece(s) |
|------------------------------------|------------|

Outputs

| | |
|-------------------------------------|------------|
| Number of digital switching outputs | 1 Piece(s) |
|-------------------------------------|------------|

Interface

| | |
|------|--------------------|
| Type | CANopen, DeviceNet |
|------|--------------------|

CANopen

| | |
|--------------------|---------------------|
| Transmission speed | 10 ... 1,000 kBit/s |
|--------------------|---------------------|

DeviceNet

| | |
|--------------------|--------------------|
| Transmission speed | 125 ... 500 kBit/s |
|--------------------|--------------------|

Connection

| | |
|-----------------------|------------|
| Number of connections | 3 Piece(s) |
|-----------------------|------------|

Connection 1

| | |
|--------------------|----------|
| Type of connection | Terminal |
| Cable gland | M16 |
| No. of pins | 8 -pin |

Connection 2

| | |
|--------------------|----------|
| Type of connection | Terminal |
| Cable gland | M16 |
| No. of pins | 5 -pin |

Mechanical data

| | |
|-----------------------|--------------------------------|
| Dimension (W x H x L) | 89.25 mm x 196.5 mm x 111.8 mm |
| Housing material | Metal |
| Net weight | 1,245 g |

Operation and display

| | |
|-----------------|------------------|
| Type of display | Bar graph LED |
|-----------------|------------------|

Environmental data

| | |
|--------------------------------|---------------|
| Ambient temperature, operation | -5 ... 50 °C |
| Ambient temperature, storage | -30 ... 70 °C |

Certifications

| | |
|--|--|
| Degree of protection | IP 65 |
| Certifications | c UL US |
| Test procedure for EMC in accordance with standard | EN 61000-6-2:2005 EN 61000-6-4:2001 |
| Test procedure for noise in accordance with standard | EN 60068-2-64 |
| Test procedure for oscillation in accordance with standard | EN 60068-2-6 |
| Test procedure for shock in accordance with standard | EN 60068-2-27 EN 60068-2-29 |

Classification

| | |
|-----------------------|----------|
| Customs tariff number | 84718000 |
| ECLASS 5.1.4 | 19039001 |
| ECLASS 8.0 | 19179090 |
| ECLASS 9.0 | 19179090 |
| ECLASS 10.0 | 19170506 |
| ECLASS 11.0 | 19170506 |
| ECLASS 12.0 | 19170506 |
| ECLASS 13.0 | 19170506 |
| ECLASS 14.0 | 19170506 |
| ETIM 5.0 | EC000515 |
| ETIM 6.0 | EC000515 |
| ETIM 7.0 | EC000515 |
| ETIM 8.0 | EC000515 |
| ETIM 9.0 | EC000515 |

Electrical connection

Connection 1

| | |
|--------------------|----------------|
| Function | Voltage supply |
| Type of connection | Terminal |
| Cable gland | M16 |
| No. of pins | 8 -pin |

Electrical connection

| Terminal | Assignment |
|----------|------------|
| 1 | OUT WARN |
| 2 | PE |
| 3 | GND |
| 4 | VIN |
| 5 | IN 1 |
| 6 | PE |
| 7 | GND |
| 8 | VIN |

Connection 2


| | |
|--------------------|----------------|
| Function | Data interface |
| Type of connection | Terminal |
| Cable gland | M16 |
| No. of pins | 5 -pin |

| Terminal | Assignment |
|----------|------------|
| 1 | V- |
| 2 | CAN L |
| 3 | Drain |
| 4 | CAN H |
| 5 | V+ |
| 6 | V- |
| 7 | CAN L |
| 8 | Drain |
| 9 | CAN H |
| 10 | V+ |

Operation and display

| LED | Display | Meaning |
|-----|---------|--------------------|
| 1 | Green | Operating mode |
| 2 | Green | PWR |
| 3 | Green | TRANSMIT DATA (Tx) |
| 4 | Green | RECEIVE DATA (Rx) |
| 5 | Yellow | BUF |
| 6 | Yellow | ERPA |
| 7 | Yellow | BOFF |

Suitable transmitters

| | Part no. | Designation | Article | Description |
|---|----------|-------------------|---------------------------|---|
|  | 50039939 | DDLS 200/200.1-50 | Optical data transmission | Special version: Operation of parallel light axes, Not influenced by reflective surfaces Working range: 200 ... 200,000 mm Transmission frequency: F1 Interface: CANopen, DeviceNet Connection: Terminal, M16 |