

Hoja técnica

Autoadhesivo

Código: 50120359

Safety Sticker Set 2

Contenido

- Datos técnicos

Leuze

Regular function test of the protective device by instructed persons (e.g. operators)

The following tests are carried out on a regular basis (e.g. daily). Make absolutely certain that no persons are located in the danger zone during the inspection.

Test at least:

- ☞ Are safety sensor and connectors securely mounted and free of obvious signs of damage, changes or tampering?
- ☞ Are possible access points free from obvious signs of modification?
- ☞ Test the effectiveness of the safety sensor:
 1. The OSSD LED on the safety sensor must illuminate green.
 2. Interrupt an active beam or the protective field with a suitable, opaque test object.
 3. Does the OSSD LED illuminate constantly red while the protective field is interrupted?

When possible, test during running operation:

- Protective device with approach function:
during machine operation, the protective field is interrupted with a suitable opaque test object - are the obviously dangerous machine parts stopped without noticeable delay?
- Protective device with presence detection:
the protective field is interrupted with a suitable opaque test object - does this prevent operation of the obviously dangerous machine parts?

If there is any doubt about the correct function of the safety system or if you answer no to one of the points, shutdown the system and inform the person responsible. More information about regular testing of the safety sensors can be found in the respective operating instructions.

Cleaning:

In the event of visible contamination, the front screens of the AOPDs are to be periodically cleaned with mild detergent. Do not use abrasive, alcohol-containing or aggressive detergents or solvents!

EN - 06/2024 A4-No. 607353-02

La figura puede variar

Datos técnicos

Datos básicos

Descripción	Indicaciones de seguridad «Comprobación regular del funcionamiento del equipo de protección»
Detalles	Etiquetas adhesivas, 12 hojas en una bolsa de plástico

Datos mecánicos

Dimensiones (An x Al x L)	100 mm x 210 mm
Peso neto	43 g
Material	Papel adhesivo de plata mate y laminado, adhesivo permanentemente

Software

Idiomas	Búlgaro
	Croata
	Danés
	Eslovaco
	Esloveno
	Estonio
	Finés
	Griego
	Holandés
	Húngaro
	Letón
	Lituano
	Rumano

Clasificación

Número de arancel	48114190
ECLASS 5.1.4	27279290
ECLASS 8.0	27279290
ECLASS 9.0	27279090
ECLASS 10.0	27273692
ECLASS 11.0	27273692
ECLASS 12.0	27273692
ECLASS 13.0	27273692
ECLASS 14.0	27273692
ECLASS 15.0	27273692
ECLASS 16.0	27273692
ETIM 5.0	EC002498
ETIM 6.0	EC003015
ETIM 7.0	EC003015
ETIM 8.0	EC003015
ETIM 9.0	EC003015
ETIM 10.0	EC003015
UNSPSC 26.08	31242100